

--	--	--	--	--	--	--	--	--	--



P.E.S. College of Engineering, Mandya - 571 401

(An Autonomous Institution affiliated to VTU, Belgaum)

Third Semester, M. Tech. - Civil Engineering (MCAD)

Semester End Examination; Dec - 2016/Jan - 2017

Advanced Design of Reinforced Concrete Structural Elements

Time: 3 hrs

Max. Marks: 100

Note: i) Answer **FOUR** full questions, choosing at least **ONE** full question from each unit.

ii) Use of IS 456 and SP 16 are permitted.

iii) Assume missing data if any.

UNIT - I

- Design a rectangular continuous beam over spans 7 m to carry a dead load 12 kN/m and a live load of 16 kN/m. The beam is continuous over more than 3 spans and is supported by columns. Use M20 concrete and Fe415 steel. 25
- A continuous beam with simple supports has two spans each of 6 m, from c/c of supports. The characteristic dead load of 15 kN/m and characteristic live load is 20 kN/m. Design the critical section of the beam and sketch the details of reinforcement. Use M20 concrete Fe500 Steel. 25

UNIT - II

- Design an interior panel of a flat slab with panel size 6 m x 6 m supported by columns of size 500 mm x 500 mm. Provide suitable drop, take live load as 4 kN/m². Use M20 concrete and Fe415 steel. Sketch details of reinforcement. 25
- Design a fixed circular slab of a water tank to suit the following data,
Slab is fixed to circular ring beam, Depth of water in the tank = 5 m
Diameter of tank (c/c of circular beam) = 8 m
Use M20 Grade concrete and Fe415 Steel. 25

UNIT - III

- The roof of an 8 m wide hall is supported on portal frame spaced at 4 m intervals. The height of the portal frame is 4 m. The continuous slab is 120 mm thick. LL on roof is 1.5 kN/m². SBC of soil is 150 kN/m². The column may be assumed as fixed. Design the column and beam members of the portal frame. Use M20 concrete and Fe415 steel, sketch the details of reinforcement. 25
- Design a slender column with biaxial bending from the following data. Use M30 Grade concrete and Fe415 steel Size of column = 6 m.
 $L_{ex} = 6$ m (Effective length for bending Parallel to larger dimension)
 $L_{ey} = 5$ m (Shorter dimension). 25
Un supported length = 7.0 m, Factored load; $P_u = 1500$ kN
Factored moment in the direction of larger dimension = 40 kN-m (TOP) and 22.5 kN-m (bottom)
Factored moment in the direction of shorter dimension = 30 kN-m (Top) 20 kN-m (bottom).

UNIT - IV

7. Design the side walls and hopper bottom of a 3 m x 3 m square bunker to store 300 kN of a coal. Density of coal is 9 kN/m^3 . Angle of repose = 30 degrees. Adopt M20 grade concrete and Fe415 steel. Sketch the details of reinforcement in the bunker. 25
8. A cylindrical silo having an internal diameter of 6 m and 20 m deep (cylindrical portion) with a conical hopper bottom. The material stored is wheat with density of 8 kN/m^3 . The co-efficient of friction between wall and material is 0.444. The ratio of horizontal to vertical pressure is 0.40. Angle to repose = 25 degrees. Adopt M20 grade concrete and Fe415 steel. Adopt Janssen's theory for pressure calculations. Sketch details of reinforcement. 25

* * *