

Note: i) *Answer FIVE full questions, selecting ONE full question from each unit. ii*) *Missing data, if any, may be suitably assumed.*

UNIT - I

- 1 a. Differentiate between statically determinate and statically indeterminate structure.
 - b. Find the force in the member of the truss shown in Fig. Q1.b. Tabulate the results. Use method of joints.



- 2 a. Derive deflection equation with usual notations.
 - b. A beam of length *L* is loaded with a couple applied at an intermediate point. Calculate the slope at the ends and the deflection under the point load of the couple. (Fig. Q2.b). Take EI constant.



3 a. For the beam in Fig. Q3.a. Compute the rotation at support and maximum deflection by moment area method. Take $I = 4 \times 10^8 \text{ mm}^4$ and E = 200 GPa.



6

14

10

Page No... 1

8

8

14

P17CV43

b. Find the slope and deflection at the free end, by moment area method for the Fig. Q3.b shown with neat sketches.



- 4 a. A simply supported beam of length *L* carries a load *L* of *W* per unit run over the whole span. Find the slope and deflection at the centre by conjugate beam method. Take EI as constant.
 - b. Find the midspan deflection of the beam shown in Fig. Q4.b. Using Conjugate beam method. Take E = 200 GPa, $I = 200 \times 10^{-4} \text{ m}^2$.



UNIT - III

- 5 a. A Symmetrical unstiffened suspension cable is parabolic in shape and has a span of 300 m and a dip of 30 m. It supports an udl of 20 kN/m over the whole span. If the maximum allowable stress
 6 is 150 N/mm², determine the length of the cable and area of the cable.
 - b. A cable is suspended from two points A and B which are 80 m apart. A is 5 m below B. The lowest point on the cable is 10 m below A. The cable supported a udl of intensity 20 kN/m over the entire span. Compute the;

i) Reaction at supports ii) Maximum tension in the cable

- 6 a. A three hinge parabolic arch has a span of 20 m and central rise of 5 m. It carries a concentrated load of 100 kN at a distance of 5 m from the left support. Determine the maximum bending 10 moment and plot the BMD.
 - b. A three hinged parabolic arch of 36 m span and central rise of 6 m carry a udl of 30 kN/m to the left half of the span and a 60 kN point load at 9 m from the right support. Determine the normal 10 thrust, radial shear and BM at quarter span from left support.

10

10

20

UNIT - IV

7 a. Two wheel loads of 160 kN (leading loads) and 400 kN spaced 2 m apart move on a simply supported beam girder of span 16 m from left to right. Find the maximum positive and negative 10 shear force at a section;

i) 4 m from the left end ii) 6 m from left end

- A UDL of intensity 2 kN/m and 5 m long crosses simply supported beam 20 m span from left to right calculate;
 - i) Maximum shear force and Maximum bending moment at a section 8 m from the left support
 - ii) Absolute maximum bending moment
- 8 a. State and prove Castigliano's first theorem.
 - b. A simply supported beam of span 20 m carries a concentrated load 10 kN at a distance 8 m from left end support. Using Castigliano's method, determine the deflection under the load. 10 Assume EI constant.

UNIT - V

9 a. Detemine the reaction components in propped cantilever shown Fig. Q9.a. EI is constant. Use consistent deformation method.

$$f = 2m \qquad b = 3m \qquad f = 3m \qquad f$$

 b. Using consistent deformation method, determine the reaction component in the beam shown in Fig. Q9.b. EI constant.



10. With neat sketch, derive three moment equation.

* * * *