

--	--	--	--	--	--	--	--	--	--



P.E.S. College of Engineering, Mandya - 571 401

(An Autonomous Institution affiliated to VTU, Belagavi)

Fourth Semester, B.E. - Mechanical Engineering

Semester End Examination; July / Aug. - 2022

Applied Thermodynamics

Time: 3 hrs

Max. Marks: 100

Note: Answer **FIVE** full questions, selecting **ONE** full question from each unit.

UNIT - I

- 1 a. Write the drawback of Carnot cycle and derive an expression for the air standard efficiency of an Otto cycle and state the assumptions made. 10
- b. An engine with 200 mm cylinder diameter and 300mm stroke works on theoretical Diesel cycle. The initial pressure and temperature of air used are 1 bar and 27°C. The cut-off is 8% of the stroke, determine;
- Pressures and temperatures at all salient points
 - Theoretical air standard efficiency 10
 - Mean effective pressure
 - Power of the engine if the working cycles per minute are 380
- Assume that compression ratio is 15 and working fluid is air. Consider all conditions to be ideal.
- 2 a. Discuss briefly any two methods employed for improvement of thermal efficiency of gas turbine plant. 10
- b. In a turbine plant working on Brayton cycle, the air inlet is 27°C, 0.1 MPa. The pressure ratio is 6.25 and the maximum temperature is 800°C. The turbine and compressor efficiencies are each 80%. Find compressor work, turbine work, heat supplied cycle efficiency and turbine exhaust temperature. Mass of air may be considered as 1 kg. Draw T-s diagram. 10

UNIT - II

- 3 a. Describe the different operation of Rankine cycle. Derive also the expression for its efficiency. 7
- b. In a steam turbine steam at 20 bar, 360°C expanded to 0.08 bar. It then enters a condenser, where it is condensed to saturated liquid water. The pump feeds back the water into the boiler. Assume ideal processes; find per kg of steam the net work and the cycle efficiency. 9
- c. Briefly explain effects of maximum pressure and maximum temperature on the performance of simple Rankine cycle. 4
- 4 a. Explain the working and analysis of the regenerative Rankine cycle with closed feed water heater. 10

- b. A turbine is supplied with steam at a pressure of 32 bar and a temperature 410°C. The steam expands isentropic ally to a pressure of 0.08 bar. Find the dryness fraction at the end of expansion and thermal efficiency of the cycle. If the steam is reheated at 5.5 bar to a temperature of 400°C and then expanded isentropic ally to a pressure of 0.08 bar, what will be the dryness fraction and thermal efficiency of the cycle. 10

UNIT - III

- 5 a. Obtain the optimum pressure ratio for minimum works in a two-stage compressor with perfect inter cooling and deduce the equation for minimum work. 12
- b. A single-acting, single-cylinder reciprocating air compressor has a cylinder diameter of 200 mm and a stroke of 300 mm. Air enters the cylinder at 1 bar; 27°C. It is then compressed polytropic ally to 8 bar according to the law $PV^{1.3} = \text{constant}$. If the speed of the compressor is 250 rpm, calculate the mass of air compressed per minute, and the power required in kW for driving the compressor. 8
- 6 a. Define the volumetric efficiency and isothermal efficiency. Explain the effect of clearance volume on volumetric efficiency of a single-stage reciprocating compressor. 10
- b. A single-acting, single-stage reciprocating air compressor of 250 mm bore and 350 mm stroke runs at 200 rpm. The suction and delivery pressures are 1 bar and 6 bar respectively. Calculate the theoretical power required to run be compressor under each of the following conditions of compression: 10
- i) Isothermal ii) Polytropic $n = 1.3$ and iii) Isentropic, $\gamma = 1.4$,
- Neglect the effect of clearance and also calculate isothermal efficiency in each of the above cases.

UNIT - IV

- 7 a. Explain the effect of superheating and sub-cooling of liquid in a refrigeration system. 10
- b. Sketch and explain the vapour compression cycle on a T-S diagram and deduce an expression for its COP. 10
- 8 a. Write short notes on the following terms: 12
- i) Properties of good refrigerant
- ii) Steam jet refrigeration
- iii) Refrigeration effect and TON of refrigeration
- b. A simple vapour compression plant produces 5 tones of refrigeration. The enthalpy values at inlet to compressor, at exit from the compressor, and at exit from the condenser are 183.19, 209.41 and 74.59kJ/kg respectively. Estimate;
- i) The refrigerant flow rate 8
- ii) The C.O.P
- iii) The power required to drive the compressor
- iv) The rate of heat rejection to the condenser

UNIT - V

- 9 a. Explain the following:
- i) The Morse test for determining the indicated power of a multi-cylinder engine 8
 - ii) Air box method to determine air consumption
- b. The following observations were made during a test on a two-stroke oil engine.
- Room temperature = 22°C, Bore = 20 cm, Stroke = 25 cm, speed = 350 rpm, Brake drum diameter = 1.2 m, Net brake load = 450 N, Mean effective pressure = 2.8 bar, Oil consumption = 3.6 kg/hr, Calorific value of oil = 41800 kJ/gk, Quantity of Jacket cooling water = 455 kg/hr, Rise in temperature o jacket water = 28°C. Temperature of exhaust gases entering and leaving the exhaust gas calorimeter are 320°C and 220°C respectively. Quantity of water passing through the exhaust gas calorimeter is 8 kg/min. Temperature rise of calorimeter water = 9°C. Determine the indicated and brake power, mechanical efficiency and brake thermal efficiency. Draw the heat balance sheet on one minute basis. 12
10. Write short notes on;
- a) Motoring Method
 - b) Basic measurements for engine performance 20
 - c) Willian's line method
 - d) Indicated power, Brake power and Friction Power

* * * *