

--	--	--	--	--	--	--	--	--	--



P.E.S. College of Engineering, Mandya - 571 401

(An Autonomous Institution affiliated to VTU, Belgaum)

Third Semester, B.E. – Automobile Engineering

Semester End Examination; Dec. - 2014

Thermodynamics

Time: 3 hrs

Max. Marks: 100

Note : i) Answer **FIVE** full questions, selecting **ONE** full question from each Unit.

ii) Assume suitable missing data if any iii) Use of Thermodynamic data hand book is permitted.

Unit - I

- 1 a. Distinguish between:
- Intensive and extensive properties.
 - Point and path functions. 8
 - Thermal and Thermodynamic Equilibrium.
 - Microscopic and Macroscopic approach.
- b. State zeroth law of thermodynamics. How does this form the basis of temperature measurement? 6
- c. A new scale N of temperature is divided in such a way that the freezing point of ice is 100° N and the boiling point is 400° N. What is the reading on this new scale when the temperature is 150° C. 6
- 2 a. What are the characteristics common between heat and work? 4
- b. Derive an expression for displacement work during polytropic process. 4
- c. A fluid undergoes the following processes in sequence to complete a cycle.
- Heated reversible at constant pressure of 1.05 bar until it has a volume of 0.02 m³.
 - It is then compressed reversible according to the law $PV = \text{const}$, to a pressure of 4.2 bar.
 - It is then allowed to expand reversible according to a law $PV^{1.3} = C$. 12
 - Finally, it is heated at constant volume back to initial conditions.
- If the work done during constant pressure process is 515 N–m. Calculate the net work done on or by the cycle.

Unit - II

- 3 a. Show that energy is a property of the system. 6
- b. A fluid is confined in a cylinder by a spring loaded friction less piston, so that the pressure in the fluid is a linear function of the volume ($P = a + bv$). The internal energy of the fluid is given by the following equation $u = 34 + 3.15 PV$, where u is in kJ, P in kPa and V in m³. If the fluid changes from an initial state of 170 kPa, 0.03m³ to a final state of 400 kPa, 0.06 m³, with no work other than that done on the piston. Find the direction and magnitude of work and heat transfer. 14
- 4 a. Derive steady flow energy equation for an open system. 8
- b. In a gas turbine installation, the gases enters the turbine at the rate of 5 kg/s with a velocity of 50m/s and enthalpy of 900 kJ/kg and leaves the turbine with 150 m/s, enthalpy of 400 kJ/kg. the loss of heat from the gases to the surroundings is 25 kJ/kg. Assume $R = 0.285$ kJ/kg-K and inlet conditions to be 100 kPa and 27°C. Determine the power developed by the 12

Unit - III

- 5 a. Give Kelvin – Plank and Clausius statement of second law of thermodynamics and show that they are equivalent. 12
- b. A domestic food freezer maintains a temp of -15°C . The ambient air temperature is 30°C . If heat leaks into the freezer at a continuous rate of 1.75 kJ/s . What is the least power necessary to pump this heat out continuously? 8
- 6 a. Define Perpetual machine of second kind. 2
- b. Explain the factors that make the process irreversible. 8
- c. A reversible heat engine operates between three heat reservoir 100 K , 800 K and 600 K and rejects heat to a reservoir at 300 K . The engine develops 10 kW and rejects 412 kJ/min . If the heat supplied by the reservoir at 100 K is 60% of heat supplied by the reservoir at 600 K , find the quantity of heat supplied by each reservoir. 10

Unit - IV

- 7 a. Derive the expression for the air standard efficiency of a Dual cycle. 10
- b. Two engines are to operate on otto and diesel cycles with the following data.
Maximum temperature : 1400 K , Exhaust temperature = 700 K , state of air at the beginning of compression 0.1 MPa , 300 K . Estimate the compression ratio, maximum pressure and thermal efficiency. 10
- 8 a. Derive the condition for minimum work output to a two stage reciprocating air compressor with perfect inter cooling. 6
- b. Obtain an expression for the volumetric efficiency of an single stage air compressor in terms of the pressure ratio, clearance and 'n' the exponent of expansion and clearance. 6
- c. A multi stage compressor comprising air is to be designed to elevate the pressure from 1 bar to 120 bar , such that the stage pressure ratio, should not exceed 4 . Determine; 8
- i) The number of stages, ii) Exact stage pressure ratio iii) intermediate pressure.

Unit - V

- 9 a. With a neat sketch, explain the working of vapour absorption refrigeration system. 8
- b. An Ammonia In plant operates between a condenser temperature of 30° and an evaporator temperature of -15°C . It produces 10 tons of ice per day from water at 30°C to ice at -5°C . Assume the state at the end of compression process as dry saturated determine;
- i) Mass flow rate of refrigerant ii) Capacity of refrigeration plant 12
- iii) COP, use the following data:
 C_p of water = 4.186 kJ/kg-K , C_p of solid ice = 1.94 kJ/kg-K
Latent heat of fusion at 0°C for water = 335 kJ/kg .
- 10 a. On a particular day, the atmospheric air was found to have a DBT of 30° and WBT of 18°C . The barometric pressure was observed to be 1.01325 bar . Using the tables of psychrometric properties of air, determine Relative humidity, the specific humidity, dew point temperature, enthalpy and volume of mixture/kg of dry air. 10
- b. Indicate the following pressure on psychometric chart: 10
- i) Adiabatic Humidification ii) Adiabatic De–Humidification
iii) Adiabatic mixing of air iv) Sensible heating.